SIL # 006 1000 Hour Preventive Maintenance Checklist Equipment: Double Barrel Drum Mixer Plant Date Issued: Revised: no Additional Equipment Operation and Service Manuals Revision #: 0

Reference:

By: Christian Johnson, Service Technician Astec Service Department

TWICE A YEAR MAINTENANCE SCHEDULE (APPROXIMATELY 1,000 HOURS)

COLD FEED SYSTEM

- ☐ CHANGE THE OIL IN GEAR REDUCERS
- ☐ VISUALLY INSPECT BIN WALLS, AND WELDS FOR WEAR

VIRGIN CONVEYOR AND SCREEN

☐ CHANGE OIL IN GEAR REDUCERS

DOUBLE BARREL DRUM MIXER

- ☐ CHANGE THE OIL IN THE PLANETARY REDUCER
- ☐ RE-GREASE INPUT SHAFT SEALS, PLANETARY REDUCER
- ☐ CHECK THE DRUM FLIGHTS, FOR WEAR AND INTEGRITY

BAGHOUSE

- ☐ CHANGE THE OIL IN SCREW DRIVE REDUCERS
- ☐ CHANGE THE OIL IN THE COMPRESSOR
- ☐ CHANGE THE COMPRESSOR OIL FILTER
- ☐ REMOVE, CLEAN, RE-GREASE EXHAUST FAN SHFT BEARINGS (Recommended by the bearing manufacturers maintenance instructions)

SILO SYSTEM

- ☐ CHANGE THE OIL IN THE DRAG REDUCER
- ☐ RE-GREASE INPUT SHAFT SEALS, DRAG REDUCER
- CLEAN AND RE-GREASE DRAG HEAD AND TAIL SHAFT BEARINGS

RECYCLE SYSTEM

- ☐ CHANGE THE OIL IN THE REDUCERS
- □ OPEN, INSPECT, CLEAN, FLUSH, AND RE-GREASE CRUSHER BEARINGS
- ☐ VISUALLY INSPECT BIN WALLS, AND WELDS FOR WEAR

RAP CONVEYOR

- ☐ CHANGE THE OIL IN THE GEAR REDUCERS
 - © Astec, Inc. 2003